



高品质 Roller 轮

- 采用Steel 轮毂，结构坚固
- 高品质聚氨酯 + 优秀的粘贴力
- 耐水，耐腐蚀性强
- 机械性优质
- 使用温度：-10 ~ +90°C

区分	轮子种类	说明	轮子外径(D) mm	轮宽(W) mm	轮厚(L) mm	轴径(A) mm	允许载重 Kg	轴承规格
HURD	HURD-80-06017	- 浇注型聚氨酯(Shore A95) - 碳钢轮毂 - 球轴承 2个	80	55	60	17	380	6005 ZZ
	HURD-80-07017		80	65	70	17	450	6005 ZZ
	HURD-80-10017		80	95	100	17	650	6005 ZZ
	HURD-80-06020		80	55	60	20	380	6005 ZZ
	HURD-80-07020		80	65	70	20	450	6005 ZZ
	HURD-80-10020		80	95	100	20	650	6005 ZZ
	HURD-85-06017		85	55	60	17	450	6005 ZZ
	HURD-85-07017		85	65	70	17	520	6005 ZZ
	HURD-85-08017		85	75	80	17	600	6005 ZZ
	HURD-85-09017		85	85	90	17	670	6005 ZZ
	HURD-85-10017		85	95	100	17	750	6005 ZZ
	HURD-85-06020		85	55	60	20	450	6005 ZZ
	HURD-85-07020		85	65	70	20	520	6005 ZZ
	HURD-85-08020		85	75	80	20	600	6005 ZZ
	HURD-85-09020		85	85	90	20	670	6005 ZZ
	HURD-85-10020		85	95	100	20	750	6005 ZZ